Specifications

Air Scrubber 750

VARIABLE

SPEED

GFCI

OPTIONAL CARBON

FILTER

Features	Air Scrubber 750	Specifications	Air Scrubber 750
High Air Volume	Y	Power Supply	220~240V/50HZ
Low AMP Draw	Y	Wattage	210W
Lightweight	Y	Filter	H13 Hepa & G4 Pre Filter
Easy Carry Handle	Y	Power Cord	1.50mm ²
Removable Front Cover	Y	Power Cord Length	5m
Cord Wrap In 4 Positions	Y	Housing	High Density Polypropylene
Variable Speed - 1/4 HP	Y	Speed	2400 RPM
Operates Vertically & Horizontally	Y	Air Volume (CFM)	750 CFM
Has H13 Hepa Filter & G4 Pre-Filter	Y	Inlet Diameter	16 Inch
High Density Polypropylene Housing	Y	Outlet Duct	Detachable
Accepts 16" Inlet Flex Duct	Y	Net Weight	16.5 Kgs
Has 10" Lay Flat Outlet Duct	Y	Gross Weight	18.5 Kgs
2 Stage Filtration	Y	Measurement	570 x 360 x 655 mm
Easily Stackable	Y	Warranty	1 Year

LORAIR

Application

The Air Scrubber 750 is the ideal choice for floor & carpet drying. It is also suitable for, janitorial, water restoration & many others. The variable speed Air Scrubber keeps high air volume with low AMP draw. It is light weight with easy to carry Handle, & functional cord wrap in 4 positions. It has 1/4HP sealed motors With variable speed, low temperature rise and long industrial use. It can be operated vertically & horizontally, and comes with a H13 Hepa filter & G4 Pre filter. Its designed to accept 16" Inlet flex duct & 10" lay flat outlet duct for a variety of set-up options. The housing is High Density Polypropylene for durability. Can be easily stacked during use, storage & transportation.

Key Design Features

SIMON 07704 509957

- The detachable outlet duct ring makes attaching lay flat duct quickly & easily.
- The large 16" diameter inlet maximizes the capture zone of airborne particles
- Lightweight and compact with High Density Polypropylene Housing for Durability.
- Can be Stacked horizontally & has an easy to carry handle.



sales@alorair.co.uk

